

# H836 Hydrogen

## Specification Sheet



<b>Instrument Range*</b>	0.0001** to 2.5 mg (1 g sample)	
<b>Precision†</b>	0.00005 mg or 2% RSD, whichever is greater	
<b>Analysis Time</b>	90 seconds (including outgas, purge, and analysis delay)	
<b>Cycle Time</b>	180 seconds (nominal)	
<b>Calibration</b>	Standards (single or multi-point); manual; gas dose	
<b>Sample Size</b>	1 g (nominal)	
<b>Detection Method</b>	Non-Dispersive Infrared Absorption	
<b>Chemical Reagents</b>	<ul style="list-style-type: none"><li>• Anhydrous Magnesium Perchlorate (MgClO<sub>4</sub>)</li><li>• Sodium Hydroxide on an Inert Base</li></ul>	<ul style="list-style-type: none"><li>• Copper Oxide, Copper Turnings</li><li>• Oxygen/Moisture Indicating Tube</li></ul>
<b>Gas Requirements</b>		
Carrier:	He: (99.99% pure), 22 psi (1.5 bar) ±5%	Ar: (99.999% pure), 22 psi (1.5 bar) ±5%
Pneumatic:	Compressed Air, 40 psi (2.8 bar) ±10%, source must be oil and water free	
<b>Gas Flow Rates</b>		
Carrier:	460 cc/minute	
Pneumatic:	280 cc/analysis	
<b>Furnace</b>	Impulse furnace with current and power control 7500 Watts maximum, liquid cooled	
<b>Coolant</b>	3.2 L LECO Coolant	
<b>Operating Conditions</b>		
Temperature	15 to 35°C (59 to 95°F)	
Rel. Humidity	20 to 80%, non-condensing	
<b>Dimensions††</b>		
Height:	36 in. (91.5 cm) nominal; 39.25 in. (100 cm) with load head cover lift engaged	
Width:	27.75 in. (71 cm)	
Depth:	30 in. (76 cm) without monitor; 31.5 in. (80 cm) with attached touch-screen monitor	
<b>Electrical Power</b>	230 V~ (+10/-15%; at max load); 50A, 50/60 Hz, Single Phase; 12,500 BTU/hr†	
<b>Weight (approximate)</b>	Analyzer: 410 lb. (186 kg) without touch-screen monitor	

\*Use the following formula to calculate element concentration:

$$\% \text{ element concentration} = ((\text{absolute element mass in mg})/(\text{sample mass in mg})) * 100$$

\*\*Lower range is calculated as 2  $\sigma$  instrument blank deviation. Method range may differ due to factors such as sample type and method parameters.

†Calculated as 1  $\sigma$  instrument blank deviation. Method precision may differ due to sample inhomogeneity or other external factors.

††Allow for a 6 in. (15 cm) minimum access area around all sides.

†Average output based on nominal operating parameters.

V~ denotes VAC.

## Part Numbers


H836-MC	H w/PC and touch-screen
H836-C	H w/PC
H836-HC	H w/PC and autocleaner
H836-HMC	H w/PC, touch-screen, and autocleaner

## Theory of Operation

The H836 Hydrogen system is designed for wide-range measurement of hydrogen content of steel, refractory metals, and other inorganic materials. The instrument features custom MS Windows®-based software designed specifically for touch operation.

A pre-weighed sample is placed in a graphite crucible which is then heated in an impulse furnace to release analyte gases. An inert gas carrier, typically helium, sweeps the liberated analyte gases out of the furnace and through a Mass Flow Controller to a detector. Oxygen present in the sample reacts with the graphite crucible to form CO and CO<sub>2</sub>, which flows through a heated reagent, where the CO is oxidized to form CO<sub>2</sub>, and H<sub>2</sub> is oxidized to form H<sub>2</sub>O. The gas then continues through a NDIR cell where H<sub>2</sub>O is detected. These analytes are then scrubbed out of the carrier gas stream.

The detection system is comprised of a single NDIR detector. NDIR cells are based on the principle that H<sub>2</sub>O absorbs infrared (IR) energy at unique wavelengths within the IR spectrum. Incident IR energy at these wavelengths is absorbed as the gases pass through the IR absorption cells. The concentration of an unknown sample is determined relative to calibration standards. To reduce interferences from instrument drift, NDIR reference measurements of pure carrier gas are made prior to each analysis.



Specifications and part numbers may change.  
Consult LECO for latest information.

3000 Lakeview Avenue • St. Joseph, MI 49085 • Phone: 800-292-6141 • Fax: 269-982-8977  
info@leco.com • www.leco.com • ISO-9001:2008 HQ-Q-994 • LECO is a registered trademark of LECO Corporation.

**LECO Corporation**

**LECO**<sup>®</sup>  
Delivering the Right Results